

SELF-ADHESIVE LAMINATES**ROLL CHARACTERISTICS**

	<i>Value</i>	<i>Tolerance</i>
Accuracy of length measurement		
Paper-based laminates	- for any length	± 1 %
Filmic laminates	- up to and including 250 m	± 2 %
	- above 250 m	± 1 %
Width		
Minimum slitting width	50 mm	
Master rolls	- trimmed rolls	
- permanent adhesive	1000 mm, 1500 mm	± 2 mm
- ultra removable adhesive	1000 mm	± 2 mm
Slit rolls	- up to and including 100 cm	± 1 mm
	- above 100 cm	± 2 mm
Number of splices		
Paper	- up to and including 1000 m	max. 1 splice/roll
	- up to and including 2000 m	max. 2 splices/roll
	- up to and including 7000 m	max. 3 splices/roll
Film	- up to and including 1000 m	max. 2 splices/roll
	- up to and including 7000 m	max. 3 splices/roll

QUANTITIES

Actual length	
Paper-based and filmic laminates	± 10 %
Supply quantity	± 10 %

STORAGE CONDITIONS

Store at a temperature of 22 °C ± 2 °C and a relative humidity of 50 % ± 5 % away from direct sunlight and heat in a dark and dry place.

Rotate stocks so that the oldest material is used first.

If the reels are not going to be used immediately, they should be stored in their original packaging, preferably on the pallet. Whenever possible reels should be stored in a horizontal position.